EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L2	3233	(route routing) adj3 (map tablelist directory instruction structure object script) and (folder group) and (@ad<"19990329" @rlad<"19990329")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 06:11
L3	5826	(route routing) adj3 (map table list directory instruction structure object script) and (folder group) and (@ad<"19990329" @rlad<"19990329")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 06:11
L4	769	(route routing) adj3 (map table list directory) and (route routing) adj3 (agent softwawre instruction structure object script) and (folder group) and (@ad<"19990329" @rlad<"19990329")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 06:12
L5	34	(route routing) adj3 (map table list directory) and (route routing) adj3 (agent softwawre instruction structure object script) and (folder) and (@ad<"19990329" @rlad<"19990329")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 06:13
L6	24	(route routing) adj3 (map table list directory) and (route routing) adj3 (agent softwawre instruction structure object script) and (folder) and (route routing) adj3 (engine server node manager handler) and (@ad<"19990329" @rlad<"19990329")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 06:24
L7	24	(route routing) adj3 (map$4 table list directory database form) and (route routing) adj3 (agent softwawre instruction structure object script) and (folder) and (route routing) adj3 (engine server node manager handler) and (sequen$4 (selected predetermined designated predefined cuatomiz$5) adj2 order) and (@ad<"19990329" @rlad<"19990329")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 06:26

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1649	routing adj3 (logic map database directory script instructions code server node device) same (sequen$4 order series) and (@ad<"19990329" @rlad<"19990329")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 09:48
L2	277	routing adj3 (logic map database directory script instructions code server node device) same (sequen$4 order series).ab,clm. and (@ad<"19990329" @rlad<"19990329")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 09:49
L3	53	routing adj3 (logic map database directory script instructions code server node device) same (sequen$4 order series).ab,clm. and (@ad<"19990329" @rlad<"19990329") and (script instructions code map) with (state event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 09:50
L4	8	routing adj3 (logic map database directory script instructions code server node device) same (sequen$4 order series).ab,clm. and (@ad<"19990329" @rlad<"19990329") and (script instructions code map) with (based accord$4 correpson$4 associate) with (state event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 09:51
L5	7	routing adj3 (logic map database directory script instructions code server node device) same (sequen$4 order series).ab,clm. and (@ad<"19990329" @rlad<"19990329") and (script instructions code map) with (based accord$4 correpson$4 associate) with (state event condition) same (event service)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 09:53
L6	10	routing adj3 (logic map database directory) and routing adj3 (script instructions code) and (operat43 distribut$3 service event)with(sequen$4 order series) and (@ad<"19990329" @rlad<"19990329") and (script instructions code map) with (based accord$4 correpson$4 associate) with (state event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 09:55

L7	4	routing adj3 (logic map database directory) and routing adj3 (script instructions code) and (operat43 distribut$3 service event) near3 (sequen$4 order series) and (@ad<"19990329" @rlad<"19990329") and (script instructions code map) with (based accord$4 correpson$4 associate) with (state event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 09:55
L8	8	routing adj3 (logic map database directory) and routing adj3 (script instructions code) and (operat43 distribut$3 service event) near5 (sequen$4 order series) and (@ad<"19990329" @rlad<"19990329") and (script instructions code map) with (based accord$4 correpson$4 associate) with (state event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 09:56
L9	8	routing adj3 (logic map database directory) and routing adj3 (script instructions code) and (operat43 distribut$3 service event) near5 (sequen$6 order series) and (@ad<"19990329" @rlad<"19990329") and (script instructions code map) with (based accord$4 correpson$4 associate) with (state event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 09:58
L10	17	routing adj3 (logic map database directory) and routing adj3 (script instructions code) and (operat43 distribut$3 service event) near5 (sequen$6 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (script instructions code map) with (based accord$4 correpson$4 associate) with (state status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 09:59
L11	17	routing adj3 (logic map database directory) and routing adj3 (script instructions code) and (operat43 distribut$3 service event) near5 (sequen$6 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (script instructions code map) with (based accord$4 correpson$4 associate) with (state$3 status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:00

L12	98	routing adj3 (logic map database directory) and routing adj3 (script instructions code) and (operat43 distribut$3 service event) near5 (sequen$6 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (based accord$4 correpson$4 associate) with (state$3 status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:05
L13	81	12 not 11	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:00
L14	81	12 not (11 microsoft.as.)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:07
L15	100	routing adj3 (logic map database directory) and routing adj3 (script instructions code) and ((operat$3 distribut$3 service event) near5 sequen$6 (assgined designated) near3 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (based accord$4 correpson$4 associate) with (state$3 status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:13
L16	84	15 not (11 microsoft.as.)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:07
L17	12	15 not (11 microsoft.as.) and routing adj (processor server engine manager handler mechanism)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:08

L18	6	routing adj3 (logic mechanism map catalog directory) and routing adj3 (script instructions code) and ((operat$3 distribut$3 service event) near5 sequen$6 (assgined designated) near3 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (based accord$4 correpson$4 associate) with (state$3 status event condition) and routing adj (processor server engine manager handler)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:17
L19	325	routing adj3 (logic mechanism map catalog directory) and routing adj3 (script instructions code processor server engine manager handler) and ((operat$3 distribut$3 service event) near5 sequen$6 (assgined designated) near3 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (state$3 status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:18
L20	263	routing adj3 (logic mechanism map catalog directory) and routing adj3 (script code processor server engine manager handler) and ((operat$3 distribut$3 service event) near5 sequen$6 (assgined designated) near3 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (state$3 status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:19
L22	0	routing adj3 (logic mechanism map catalog directory) same routing adj3 (script agent code processor server engine manager handler) same ((operat$3 distribut$3 service event) near5 sequen$6 (assgined designated) near3 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (state$3 status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:19

L23	35	routing adj3 (logic mechanism map catalog directory) same routing adj3 (script agent code processor server engine manager handler) and ((operat$3 distribut$3 service event) near5 sequen$6 (assgined designated) near3 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (state$3 status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:20
L24	32	routing adj3 (logic mechanism map catalog directory database) same routing adj3 (script agent code) and ((operat$3 distribut$3 service event) near5 sequen$6 (assgined designated) near3 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (state$3 status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:22
L25	0	routing adj3 (scenario object plan logic map catalog directory database) same (multi$3 different plurality more various variety) adj3 routing adj3 (mechanism script agent code) and (sequen$6 (assgined designated) near3 order series round adj robin) and (@ad<"19990329" @rlad<"19990329") and (state$3 status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:25
L26	6	routing adj3 (scenario object plan logic map catalog directory database) and (multi$3 different plurality more various variety) adj3 routing adj3 (mechanism script agent code) and (sequen$6 (assgined designated) adj53 (order series) round adj robin) and (@ad<"19990329" @rlad<"19990329") and (state$3 status event condition)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/02/27 10:26